



VPZVC.EX776 Valves, Dry-pipe

[Page Bottom](#)

Valves, Dry-pipe

[See General Information for Valves, Dry-pipe](#)

VIKING CORP

EX776

210 N INDUSTRIAL PARK RD
HASTINGS, MI 49058 USA

Model E-1 in nominal pipe size 6; Model E-2 in nominal pipe sizes 3 and 4; Model F-1 in nominal pipe sizes 4 and 6 with flanged inlets and flanged or grooved outlets; Models E-1 and E-2 may be preassembled with copper trim. Maximum working pressure 1210 kPa.

[Last Updated](#) on 2004-02-27

[Questions?](#)

[Notice of Disclaimer](#)

[Page Top](#)

[Copyright © 2006 Underwriters' Laboratories of Canada®](#)

The appearance of a company's name or product in this database does not in itself assure that products so identified have been manufactured under ULC's Follow-Up Service. Only those products bearing the ULC Mark should be considered to be Listed and covered under ULC's Follow-Up Service. Always look for the Mark on the product.

ULC permits the reproduction of the material contained in the Online Certification Directory subject to the following conditions: 1. The Guide Information, Designs and/or Listings (files) must be presented in their entirety and in a non-misleading manner, without any manipulation of the data (or drawings). 2. The statement "Reprinted from the Online Certifications Directory with permission from Underwriters Laboratories' of Canada" must appear adjacent to the extracted material. In addition, the reprinted material must include a copyright notice in the following format: "Copyright © 2007 Underwriters Laboratories' of Canada®"

An independent organization working for a safer world with integrity, precision and knowledge.

