

# CERTIFICATE OF COMPLIANCE

**Certificate Number** 20121115-EX3836  
**Report Reference** EX3836-20060803  
**Issue Date** 2012-NOVEMBER-15

**Issued to:** VIKING CORP  
210 N INDUSTRIAL PARK RD  
HASTINGS MI 49058


**This is to certify that representative samples of** RESIDENTIAL AUTOMATIC SPRINKLERS  
See Addendum Page

Have been investigated by UL in accordance with the Standard(s) indicated on this Certificate.

**Standard(s) for Safety:** Standard for Residential Sprinklers for Fire Protection Service UL1626  
Canadian National Standard for Residential Sprinklers for Fire Protection Service ULC/ORD C1626

**Additional Information:** See the UL Online Certifications Directory at [www.ul.com/database](http://www.ul.com/database) for additional information

Only those products bearing the UL Listing Mark for the US and Canada should be considered as being covered by UL's Listing and Follow-Up Service meeting the appropriate requirements for US and Canada.

The UL Listing Mark for the US and Canada generally includes: the UL in a circle symbol with "C" and "US" identifiers:  the word "LISTED"; a control number (may be alphanumeric) assigned by UL; and the product category name (product identifier) as indicated in the appropriate UL Directory.

Look for the UL Listing Mark on the product.



William R. Carney, Director, North American Certification Programs  
UL LLC

Any information and documentation involving UL Mark services are provided on behalf of UL LLC (UL) or any authorized licensee of UL. For questions, please contact a local UL Customer Service Representative at [www.ul.com/contactus](http://www.ul.com/contactus)



# CERTIFICATE OF COMPLIANCE

**Certificate Number** 20121115-EX3836  
**Report Reference** EX3836-20060803  
**Issue Date** 2012-NOVEMBER-15

This is to certify that representative samples of the product as specified on this certificate were tested according to the current UL requirements.

VK457 and VK4570, concealed pendent style sprinkler, discharge coefficient "K" = 4.9, fusible link heat responsive element, 165°F temperature rated residential type sprinklers with a 135°F concealed coverplate assembly.

VK474 and VK4740, concealed pendent style sprinkler, discharge coefficient "K" = 5.8, fusible link heat responsive element, 165°F temperature rated residential type sprinklers with a 135°F concealed coverplate assembly.

VK488, concealed pendent style sprinkler, discharge coefficient "K" = 3.0, fusible link heat responsive element, 165°F temperature rated residential type sprinklers with a 135°F concealed coverplate assembly.



William R. Carney, Director, North American Certification Programs  
UL LLC

Any information and documentation involving UL Mark services are provided on behalf of UL LLC (UL) or any authorized licensee of UL. For questions, please contact a local UL Customer Service Representative at [www.ul.com/contactus](http://www.ul.com/contactus)

