

VK494 concealed residential pendent offers installation benefits

The cULus Listed VK494 Flat Plate Concealed Pendent Sprinkler is designed for installation on concealed pipe systems where the appearance of a smooth ceiling is desired. The VK494 offers sprinkler contractors advantages at 16 x 16 ft. coverage areas, addressing water supply concerns and presenting an ideal solution for homeowners.

Features and advantages of Viking's K4.9 residential concealed pendent sprinkler:

- Optimized at a 16 x 16 ft. coverage area, making it an ideal solution for areas where water supply issues may be present
- cULus Listed for residential applications and available in a corrosion resistant Electroless Nickel PTFE (ENT) coating for areas where corrosion is a concern
- Protective cap prevents damage during installation and ceiling finishing as well as paint overspray from coating critical internal parts
- Available in Ordinary 155°F (68°C) and Intermediate 200°F (93°C) temperature ratings with a 1/2" NPT threaded connection
- Maximum working pressure of 175 psi (12 bar)

For more information, please contact your Viking sales representative or visit our website at **vikinggroupinc.com**.

TECHNICAL SPECIFICATIONS

Model Number: VK494
Base Part Number: 23707

Listings/Approvals: cULus Listed

K-factor: K4.9 (70.6)

Connection: 1/2" NPT 15 mm BSPT

155°F (68°C)

200°F (93°C)

Operating Element: Glass Bulb

Finish: Brass, ENT Coated

Item Price Group: V182

Occupancy/Hazard: Residential

Technical Datasheet: F 012116

Installation Wrench 23143, 22978M/B

DIGITAL TOOLS

Temperatures:



Viking's revolutionary Sprinkler Selector ensures that you can find the right sprinkler for the job — every time. Get started by visiting webtools.vikingcorp.com/sprinklerselector.

VKG-000

General reference only. Prior to the design, layout, and/or installation of any sprinkler system, please refer to Viking's technical documentation and consult with the AHJ.



