



Corrosion Resistance | Fusible Link Stainless Steel Sprinkler

Viking's Model VK368 Standard Response Stainless Steel Sprinkler with a fusible link operating element is the first of its kind in the fire protection industry. The 8.0 K-factor sprinkler features a stainless steel sprinkler body, deflector, and seat, with a solder link operating element. This makes the sprinklers well-suited for environments like food processing facilities, where harsh, corrosive chemicals are used for cleaning purposes and exposure to glass can be a concern.

- First-in-the-Industry combination of stainless steel frame and solder link operating element makes the sprinkler ideal for food processing applications.
- cULus Listed for protection of corrosive environments.
- Available in an intermediate temperature rating of 205 °F (96 °C).
- Features a 3/4 inch NPT (20 mm BSPT) thread size and 8.0 K-factor.
- Stainless steel sprinkler joins Viking's wide selection of corrosion resistant sprinkler options including "Electroless Nickel PTFE" (ENT) plated sprinklers, which are available throughout a significant portion of the Viking sprinkler product line.

Listings/Approvals: cULus Listed

K-factor: 8.0 (115)

Connection: 3/4" NPT
20 mm BSP

Temperature: 205°F (96°C)

Operating Element: Fusible Link

Finish: Stainless Steel

Item Price Group: V110

Occupancy/Hazard: Corrosive Environments

Technical Datasheets: F_071917

Base Part Number: 21928

MKT-0030

General reference only. Prior to the design, layout, and/or installation of any sprinkler system, please refer to Viking's technical documentation and consult with the AHJ.

Contact your local Viking SupplyNet team to place an order today!

The Viking Corporation

210 N. Industrial Park Drive, Hastings, MI 49058

Telephone: (269) 945-9501

www.vikinggroupinc.com

Trusted above all.™

